

# SpeedDeck

DESIGNED &  
MANUFACTURED  
IN THE UK

## SpeedDeck Features:

- **Portable:** Designed to be easily set up and dismantled in seconds, by a small team or by an individual.
- **Unique SpeedLock System:** Operated from above the stage, SpeedLocks rapidly reduce the required set up time.
- **Versatile:** Construct any configuration to your requirements.



SpeedLock



Custom platform shapes, sizes, finishes, and leg heights available

	1x1m / 3.3x3.3'	2x1m / 6.6x3.3'	4x4' / 1.2x1.2m	8x4' / 2.4x1.2m
<b>Technical Specification</b>				
<b>Module weight</b>	22kg / 48.5lbs	37kg / 81.6lbs	23kg / 50.7lbs	53kg / 116.8lbs
<b>Stacking height</b>	99mm / 3.9in	99mm / 3.9in	99mm / 3.9in	99mm / 3.9in
<b>Maximum uniformly distributed load</b>	7.5kN/m <sup>2</sup> / 156 lbf/ft <sup>2</sup>	7.5kN/m <sup>2</sup> / 156 lbf/ft <sup>2</sup>	7.5kN/m <sup>2</sup> / 156 lbf/ft <sup>2</sup>	7.5kN/m <sup>2</sup> / 156 lbf/ft <sup>2</sup>
<b>Maximum point load (on 50x50mm / 2x2" square) in middle of plywood</b>	2.4kN / 539lbf	2.4kN / 539lbf	2.4kN / 539lbf	2.4kN / 539lbf
<b>Maximum point load (on 50x50mm / 2x2" square) along the edge of the platform</b>	3.6kN / 809lbf	3.6kN / 809lbf	3.6kN / 809lbf	3.6kN / 809lbf
<b>Maximum height without diagonal bracing when loaded with 7.5kN/m<sup>2</sup> / 156 lbf/ft<sup>2</sup></b>	1.2m / 47.2in	0.9m / 35.4in	1.2m / 47.2in	0.9m / 35.4in
<b>Maximum height without diagonal bracing when loaded with 5kN/m<sup>2</sup> / 104 lbf/ft<sup>2</sup></b>	1.2m / 47.2in	1.2m / 47.2in	1.2m / 47.2in	0.9m / 35.4in
<b>Maximum height without diagonal bracing when loaded with 4kN/m<sup>2</sup> / 83.5 lbf/ft<sup>2</sup> and sharing legs</b>	0.6m / 23.6in	0.6m / 23.6in	0.6m / 23.6in	n/a
<b>General</b>				
<b>Warranty</b>	5 years	5 years	5 years	5 years
<b>Applicable Standards</b>	EN13782	EN13782	EN13782	EN13782
<b>Product code</b>	140Q01	140Q02	140Q03	140Q04

Also available

### Choral Riser

Product code:  
140Q9130H



### SpeedDeck Accessories:

Handrails, Steps, Ramps, Skirt, Storage Accessories, and more.

sales@ratstands.com | +44 (0)20 8741 4804

[www.ratstands.com](http://www.ratstands.com)

All product specifications, statements, information and data (collectively, the "Information") in this data sheet are subject to change. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

SpeedDeck

# SpeedDeck Light

DESIGNED &  
MANUFACTURED  
IN THE UK

## SpeedDeck Light Features:

- **Lightweight:** Our lightest ever staging system designed for an easy one person set up.
- **Storage and Mobility:** The decks are easy to pick up and transport between events, and can be stacked for storage.
- **Space Saving:** Under platform leg storage and unique stage mounted accessories saves space on the floor and riser.
- **Quick and Easy:** 2-step under stage connectors to lock platforms together securely.
- **Ethically Made:** Constructed from recycled aluminium.



	1x1m / 3.3x3.3'	2x1m / 6.6x3.3'
<b>Construction</b>		
<b>Material of frame</b>	Aluminium Alloy	Aluminium Alloy
<b>Technical Specification</b>		
<b>Module weight</b>	Hexaboard: 15.4kg / 34lbs Carpet: 15.3kg / 33.7lbs	Hexaboard: 27.3kg / 60.2lbs Carpet: 27kg / 59.5lbs
<b>Stacking height</b>	99mm / 3.9in	99mm / 3.9in
<b>Maximum uniformly distributed load</b>	5kN/m <sup>2</sup> / 104 lbf/ft <sup>2</sup>	5kN/m <sup>2</sup> / 104 lbf/ft <sup>2</sup>
<b>Maximum point load (on 50x50mm / 2x2" square) in middle of plywood</b>	1.4kN / 314lbf	1.4kN / 314lbf
<b>Maximum point load (on 50x50mm / 2x2" square) along the edge of the platform</b>	1.5kN / 337lbf	1.5kN / 337lbf
<b>Maximum height without diagonal bracing when loaded with 5kN/m<sup>2</sup> / 104 lbf/ft<sup>2</sup></b>	1m / 3.3ft	1m / 3.3ft
<b>General</b>		
<b>Warranty</b>	5 years	5 years
<b>Applicable Standards</b>	EN13782	EN13782
<b>Product code</b>	140Q01	140Q02

Also  
available

### DrumDeck

Product code: DD22300



### SpeedDeck Light Accessories:

Attachments for mic stands, music stands, tablet stands, and speakers are available to connect to the side of the stage.

sales@ratstands.com | +44 (0)20 8741 4804

[www.ratstands.com](http://www.ratstands.com)

All product specifications, statements, information and data (collectively, the "Information") in this data sheet are subject to change. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

**SpeedDeck**